

Material Safety Data Sheet

May be used to comply with OSHA's
Hazardous Communication Standard, 29 CFR 1910.1200

NPCA Hazardous Materials Identification System

Specific Hazard	Personal Protection
4-Severe	X-Ask a supervisor
3-Serious	A-Safety Glasses
2-Moderate	B-Goggles, Glasses
1-Slight	A-Goggles, Glasses, Apron
0-Minimal	D-Goggles, Glasses, Apron, & Faceshield

IDENTITY (As used on LABELS and LIST)

Rhapsody or FINISH SUPREME Sealer / Finish P525

Health (1) Reactivity (0)
Flammability (0) Personal Protection (B)

CLP-P525
CLP-P525-5

SECTION I

MFGR'S NAME AND ADDRESS: CleanPak Products
5408 N 59TH ST. TAMPA, FL 33610

EMERGENCY TELEPHONE NUMBER: 800-424-9300 **DATE PREPARED:**
Telephone Number For Information: 813-740-8611 06-03-07

SECTION II-HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Hazardous Components	OSHA	PEL	ACGIH	Other	%Optional
Specific Components				Limits	
Specific Chemical Identity				Recommended	
Common Name(s)					
DEG Methyl Ether			NE		2-5
CAS # 111773					
Tributoxyethyl			NE		1-5
CAS #78513					
Zinc Ammonium Carbonate			25ppm(NH ₃)		1-5
CAS #38714475					
Dibutyl Phthalate			5mg/M ₃		1-5
CAS #84742					

SECTION III-PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT (F)	Over 212 ⁰ F	SPECIFIC GRAVITY (H₂O=1)	1.055
VAPOR PRESSURE (mmHg)	Not Determined	Percent Volatiles	66-68%
VAPOR DENSITY (air=1)	Less than Air	EVAPORATION POINT	Slower than n-Butyl Acetate
SOLUBILITY IN WATER	Complete	(Butyl Acetate=1)	
Total VOC's	163g/L		
APPEARANCE AND ODOR: White milky liquid with a typical acrylic odor.			

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED)	FLAMMABLE LIMITS	LEL	UEL
None	N/A	N/A	N/A

EXTINGUISHING MEDIA: Water Fog, Carbon Dioxide or Dry Chemical

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode when fighting fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION V -REACTIVITY DATA RHAPSODY OR FINISH SUPREME P525

STABILITY: UNSTABLE () **CONDITION TO AVOID:**
 STABLE (X) None

INCOMPATIBILITY (Materials to Avoid)

Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Release carbon monoxide, carbon dioxide and unidentified organic compounds.

HAZARDOUS May Occur () **CONDITIONS TO AVOID:**
Polymerization May Not Occur (X) None

SECTION VI-HEALTH HAZARD DATA

ROUTE(S) OF ENTRY:

INHALATION: Yes

SKIN: Yes

INGESTION: Yes

Health Hazards (Acute and Chronic)

Continuous skin contact may cause dermatitis. May also result in irritation to eyes and respiratory tract.

CARCINOGENICITY: NTP IARC Monographs? OSHA Regulated?
 No No No

SIGNS AND SYMPTOMS OF EXPOSURE:

Eyes: Can cause mild to moderate irritation.

Skin: Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

Breathing: Excessive inhalation of vapors can cause nasal and respiratory irritation.

Swallowing: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Medical problems of the skin, eyes or respiratory track may become aggravated.

EMERGENCY AND FIRST AID PROCEDURES:

SKIN: Wash thoroughly with water. Wash clothing before reuse. If irritation continues, call a physician.

EYE: Irrigation of the eye immediately with water for 10 minutes is good safety practice.

INGESTION: Seek medical attention. Unless advised otherwise, induce vomiting by giving either syrup of ipecac followed by 2 glasses of water of by sticking finger down throat. Do not give anything by mouth to a person who is drowsy, unconscious or has no gas reflex.

INHALATION: Remove to fresh air if effects occur. If respiration stops, give mouth-to-mouth resuscitation. Administer oxygen if available. Call a physician and/or transport to medical facility.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop discharge, if it can be performed safely, and contain material. If a substantial quantity is spilled, recover with pump or vacuum. Otherwise, use an absorbent material. Place contaminated material in a suitable for disposal. DO NOT flush to sewer or other bodies of water.

WASTE DISPOSAL METHOD:

Dispose of waste in accordance with Federal, State, and Local ordinances.

PRECAUTION TO BE TAKEN IN HANDLING AND STORING:

Keep container tightly closed, cool, dry and away from sources of ignition. Use and store with adequate ventilation.

OTHER PRECAUTIONS: All precautions in this MSDS must be observed.

SECTION VIII- CONTROL METHODS

RESPIRATORY PROTECTION:

(Specific Type): If TLV of the product or any component is exceeded, a NIOSH/MSHA jointly approved air-supplied respirator is advised. Engineering or administrative controls should be implemented to reduce exposure.

VENTILATION: Provide sufficient ventilation to maintain exposure below TLV(s).

LOCAL EXHAUST:	Adequate	SPECIAL:	None
MECHANICAL (General)	Adequate	OTHER:	None

PROTECTIVE GLOVES: Wear chemical resistant gloves such as nitrile rubber.

EYE PROTECTION: Chemical splash goggles are advised.

OTHER PROTECTIVE EQUIPMENT: Wear impervious clothing and boots.

WORK/HYGENIC PRACTICES: Wash thoroughly after handling.

We believe all information given is accurate. It is offered in good faith, but without guarantee. Since conditions are beyond our control, user assumes all responsibility and risk.