

# Material Safety Data Sheet

May be used to comply with OSHA's  
Hazard Communication Standard, 29 CFR 1910.1200

Product name or number as it appears on label

## MEGA STRIP OR STRIP EASE OR VANISH P500

### NPCA Hazardous Materials Identification System

Specific Hazard	Personal Protection
4-Severe	X-Ask a supervisor
3-Serious	A-Safety Glasses
2-Moderate	B-Goggles, Gloves
1-Slight	C-Goggles, Gloves, Apron
0-Minimal	D-Goggles, Gloves, Apron, & Faceshield

Health (3)      Reactivity (1)  
Flammability (0)      Personal Protection (B)

### SECTION I

MFGR'S NAME AND ADDRESS:

CleanPak Products  
5408 N 59<sup>TH</sup> STREET, TAMPA, FL 33610

EMERGENCY TELEPHONE NUMBER:  
FOR ADDITIONAL INFORMATION

800-424-9300  
813-740-8611

Date Prepared:  
10-15-10

### SECTION II - HAZARDOUS INGREDIENTS/ IDENTITY INFORMATION

Hazardous Components	OSHA PEL	ACGIH	TLV	Other	% Optional
Specific Chemical Identity	LIMITS				
Common Name(s)	Recommended				
Monoethanolamine, Colamine	3ppm	3ppm			10.00
CAS # 141-43-5					
*2-Butoxyethanol	50ppm	75ppm			60.00
CAS # 111-76-2					

\*This mixture contains 60.00% of 2-Butoxyethanol which subject to the reporting requirements of section 313 of Title III of the Superfund Amendments of Reauthorization Act of 1986 and 40 CFR, Part 372.

### SECTION III-PHYSICAL/CHEMICAL CHARACTERISICS

BOILING POINT (F) Over 212 F      SPECIFIC GRAVITY (H2O=1) 0.985  
VAPOR PRESSURE (mm Hg.) N/A      MELTING POINT N/A  
VAPOR DENSITY (air = 1) N/A      EVAPORATION RATE Less than 1  
SOLUBILITY IN WATER 100%      (Butyl Acetate = 1)  
APPEARANCE AND ODOR: Clear, colorless liquid with a mild odor.

### SECTION IV- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED)      FLAMMABLE LIMITS      LEL      UEL  
None      N/A      N/A      N/A

EXTINGUISHING MEDIA: Form or Carbon Dioxide Dry Foam

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode when fighting fires

UNUSUAL FIRE AND EXPLOSION HAZAORDS: Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames, and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum ( even empty) because product (even just residue) can ignite explosively.

### SECTION V - REACTIVITY DATA Mega Strip or Strip Ease or Vanish (P500)

STABILITY: UNSTABLE ( )  
STABLE (x)

CONDITONS TO AVOID:  
None

#### INCOMPATIBILITY (MATERIALS TO AVOID)

Strong mineral acids, strong organic acids, and oxidizers.

#### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

##### Sulfur Dioxide and Hydrogen Sulfide

HAZARDOUS May Occur ( ) Conditions to Avoid:  
Polymerization May Not Occur (x) Extreme Heat N/A

### SECTION VI - HEALTH HAZARD DATA

#### ROUTES (S) OF ENTRY:

INHALATION : YES

SKIN: YES

INGESTION: YES

#### Health Hazards (Acute and Chronic)

Eyes: Causes burns. Skin: Can cause irritation. Burns: Can result form prolonged exposure.

Breathing: Excessive inhalation of vapors can cause nasal and respiratory damage.

Swallowing: Can cause result in damage to throat and esophagus.

CARCINOGENICITY: NTP? IARC Monographs? OSHA Regulated?  
No No No

SIGNS AND SYMPTOMS OF EXPOSURE: See health hazards above.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known.

#### EMERGENCY AND FIRST AID PROCEDURES:

**Eyes:** Irrigation of the eye immediately with water for 15 minutes, lifting upper and lower lids occasionally. Get immediate medical attention.

**Inhalation:** If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention.

**Ingestion:** If swallowed, do not induce vomiting. Vomiting will cause further damage to throat. Dilute by giving water. Give milk of magnesia. Keep warm and quiet. Get medical attention.

### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Absorb liquid with floor absorbent and collect for disposal.

**WASTE DISPOSAL METHOD:** Dispose of waste in accordance with Federal, State and Local ordinances.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Keep container tightly closed, cool, dry, and away from sources of ignitions.

**OTHER PRECAUTIONS:** Always use good hygiene practices. All precautions in this MSDS must be observed.

### SECTION VIII - CONTROL MEASURES

#### RESPIRATORY PROTECTION

(SPECIFY TYPE): self-contained breathing apparatus in high concentrations.

LOCAL EXHAUST: Sufficient

SPECIAL : NONE

MECHANICAL (GENERAL): Sufficient

OTHER: NONE

PROTECTIVE GLOVES: Rubber.

EYE PROTECTION: Safety Glasses

OTHER PROTECTIVE EQUIPMENT: Wear clothing designed to prevent skin and eye contact..

WORK / HYGIENIC PRACTICES: Wash THOROUGHLY after handling.

We believe all information given is accurate. It is offered in good faith, but without guarantee. Since conditions are beyond our control, user assumes all responsibility and risk.